

# TECHNICAL DATA SHEET

## FIREFLY FIX 55 LIGHT TOWER





### **LED light head**

*High-strength die-cast aluminum body rated IP67 with a lifespan of 85,000 hours*

### **Lifting**

*Galvanized pole with manual lifting system, can reach a maximum extension of 5.5 m*

### **Holes**

*4 base holes for mounting the light tower on generators or external supports.*

<b>Galvanized pole features</b>	
<b>Height</b>	5,5 / 7 m
<b>Lifting system</b>	Manuale
<b>Rotation</b>	360°
<b>Aerodynamic resistance</b>	80 km/h



<b>LED</b>	<b>LUMEN</b>	<b>ILLUMINATED AREA</b>
4x75W LED	55.000 lm	1500mq - 3000mq
4x160W LED	90.000 lm	2400-4700mq
4x240W LED	160.000 lm	3500-7000mq

<b>Frequency</b>	50 Hz (available in 60 Hz)
<b>Voltage</b>	230 V (available in 110 V)
<b>Power</b>	/
<b>Operating temperature</b>	-30/ +50
<b>Noise emissions</b>	0 db
<b>Consumption</b>	
4X75W LED	0.3 KW
4X160W LED	0.68KW
4X240W LED	0.96 KW

<b>Cart</b>	Stationary
<b>Stabilizers</b>	/
<b>Tires</b>	/
<b>Base</b>	4 mounting holes
<b>Painting</b>	/