

TECHNICAL DATA SHEET

OROFLEX DRAG PIPE





OROFLEX DRAG - High-quality flat extruded polyurethane hose

Nominal inner diameter		Wall thickness		Working pressure		Burst pressure		Tensile strength		Nominal weight		Bending radius at operating pressure	
<i>mm</i>	<i>inch</i>	<i>mm</i>	<i>inch</i>	<i>Bar</i>	<i>Psi</i>	<i>Bar</i>	<i>Psi</i>	<i>Kg</i>	<i>Lb</i>	<i>Kg/m</i>	<i>Lb/ft</i>	<i>M</i>	<i>Ft</i>
102	4"	3,9	0,154	17	245	42	600	13,100	28,900	1,45	0,97	1,75	5,74
115	4"1/2	3,9	0,154	14	200	35	500	18,000	39,700	1,60	1,08	1,80	5,91
127	5"	3,9	0,154	14	200	35	500	18,000	39,700	1,70	1,14	1,90	6,23
140	5"1/2	3,9	0,154	12	175	30	435	20,000	44,100	2,00	1,34	1,95	6,40
152	6"	4,4	0,154	12	175	30	435	25,000	55,100	2,10	1,41	2,00	6,56
178	7"	4,6	0,181	11	160	28	400	33,600	74,100	2,90	1,95	2,05	6,73

OROFLEX DRAG EXTREME - High-quality flat extruded polyurethane hose

Nominal inner diameter		Wall thickness		Working pressure		Burst pressure		Tensile strength		Nominal weight		Bending radius at operating pressure	
<i>mm</i>	<i>inch</i>	<i>mm</i>	<i>inch</i>	<i>Bar</i>	<i>Psi</i>	<i>Bar</i>	<i>Psi</i>	<i>Kg</i>	<i>Lb</i>	<i>Kg/m</i>	<i>Lb/ft</i>	<i>M</i>	<i>Ft</i>
102	4"	3,9	0,154	17	245	42	600	13,100	28,900	1,50	1,01	1,90	6,23
115	4"1/2	3,9	0,154	14	200	35	500	18,000	39,700	1,60	1,08	1,95	6,40
127	5"	3,9	0,154	14	200	35	500	18,000	39,700	1,70	1,14	1,90	6,23
152	6"	4,4	0,154	12	175	30	435	25,000	55,100	2,10	1,41	2,00	6,56